



## GENERAL SPECIFICATIONS

• L.O.A	9,53m	31'3"
• Hull length	8,99m	29'6"
• L.W.L.	8,65m	28'5"
• Beam (max)	2,99m	9'10"
• Deep draft (Cast iron)	1,88m	6'2"
• Deep ballast weight	973kg	2,144 lbs
• Shallow draft (Cast iron)	1,30m	4'3"
• Shallow ballast weight	1 150kg	2,535 lbs
• Lifting keel version (Ballast melting)	0,95 - 2,33m	3'1" - 7'8"
• Lifting keel version ballast weight	1 300kg	2,865 lbs
• Air draft	13,66m	44'10"
• Light displacement	3 995kg	8,805 lbs
• Fuel capacity (standard)	130L	34 US Gal
• Fresh water capacity (standard)	160L	42 US Gal
• Engine power:		
- standard ( <i>Approved for inland waters only</i> )	14 HP	14 HP
- Option	21 HP	21 HP

## ARCHITECTS / DESIGNERS

- Naval Architect: Pascal Conq
- Interior design: Nauta Design

## EC CERTIFICATION

- Category B - 6 people
- Category C - 8 people
- Category D - 10 people

## STANDARD SAILS DIMENSIONS

• Square top mainsail	23,80m <sup>2</sup>	256 sq/ft
• Furling mainsail	18,80m <sup>2</sup>	202 sq/ft
• Self-tacking jib	15,70m <sup>2</sup>	169 sq/ft
• Genoa (105 %)	22,10m <sup>2</sup>	238 sq/ft
• Code 0	34,80m <sup>2</sup>	374 sq/ft
• Asymmetric spinnaker	70,00m <sup>2</sup>	753 sq/ft
• I	11,02m	36'2"
• J	3,87m	12'8"
• P	10,81m	35'6"
• E	3,27m	10'9"

## STANDARD EQUIPMENT

### CONSTRUCTION

- Design in accordance with European Directive requirements and according to CE certification
- Monolithic hull design in polyester
- Monolithic contact structural counter mould (Fabrics - resin) bonded to the hull
- Fiberglass and foam sandwich contact deck - coated with "diamond point" type non-slip
- Deck hull link bonded and screwed
- Cast iron keel fixed with bolts and stainless steel backing plates
- Twin rudders hung with stainless steel stock
- White coloured hull - Grey metal hull graphics
- 2 Hull portholes

### DECK EQUIPMENT

#### RIGGING

- Standard mast 9/10 anodized aluminium installed on the deck, 1 Set of spreader
- Anodised aluminium boom
- Discontinuous stainless steel standing rigging (Forestay- Side shrouds)
- No backstay
- 1 Standard fore stay
- 1 Rigid boom vang with tackle
- 1 Jib furler with drum on deck
- 2 Mainsail sheet padeyes
- 1 Self-tacking jib sheet track with traveller attached to the deck
- Maneuvers brought back to roof (except boom topping lift - foot)
- Complete running rigging:
  - 1 Main halyard
  - 1 Jib halyard with cleat and mast cleat
  - 1 Boom topping lift with cleat on mast
  - 1 Mainsail outhaul
  - 1 Mainsail sheet (bridle on the roof)
  - 2 Jib sheets
  - 2 Rapid reefing lines
- 5 Clutches (to port)

#### WINCHES

- 1 Self tailing winch (H20.1 STA) on the coachroof (Port)
- 1 Aluminium Harken B8 winch handle
- 1 Winch handle box

#### SAILS

- Self-tacking Jib on a furler Dacron with UV Natural protection, horizontal section
- Classic square topped mainsail (900 mm), semi battened with slides, Natural UV protection, horizontal section
- Lazy Jack and Lazy Bag in Natural colour

#### MOORING LINES - MOORING

- Self-draining chain locker - Clench bolt - Hatch cover
- Single roller stainless steel bow fitting with offset roller
- 6 Aluminium mooring cleats - Stainless steel chafing plate

#### SAFETY ON DECK

- Stainless steel pulpit 2 sections
- 2 Stainless steel pushpits
- 1 Lifebuoy support bracket
- Welded ring on pushpit for flag
- Double guard lines and stainless steel stanchions
- Emergency ladder on pushpit

#### COCKPIT

- Self-draining cockpit in polyester
- 1 Starboard locker (Sail locker, Life raft storage)
- 1 Single gas compartment on the port side
- 1 Gas compartment under port helmsman seat
- Natural solid wood slatted cockpit benches
- Stainless steel tiller with telescopic tiller extension
- 1 Steering compass on the roof (Starboard)
- Engine throttle and control panel on starboard
- 2 Deck access for emergency tiller
- 1 Emergency tiller
- PMMA companionway hatch and door with guillotine door and height-adjustable coaming

#### SWIM PLATFORM / STERN DECK (in trim level)

- Tilting transom with full opening (1,90m x 0,35m / 6'3" x 1'2")
- Manual control opening
- Natural solid wood sole

**INTERIOR**

- Alpi white oak joinery
- Brown oak laminated floors
- Upholstery padding: Taupe
- Interior cushions in cloth: Néo 05

**COMPANIONWAY**

Headroom: 1,89m / 6'2"

- GRP saloon companionway coated with non-slip surface on the 3 steps
- 2 Stainless steel handrails covered with anthracite leather

**SALOON**

Headroom: 1,90 - 1,85m / 6'3" - 6'1"

- 2 Lengthways saloon bench seats
- Saloon table with 2 folding seats, bottle rack and central storage
- Storage under bench seats
- Indirect LED lighting above the benches
- 2 LED ceiling lights
- 1 USB socket on the electrical panel
- 2 Panoramic roof windows
- 2 Hull portholes
- 1 Opening deck hatch with ventilator, T44

**GALLEY - PORT**

Headroom: 1,85m / 6'1"

- L-shaped galley
- Worktop in compact Clay with painted wooden fiddles
- 1 1 rectangular stainless steel sink (350mm x 320mm / 1'2" x 1'1")
- 1 Mixer tap with hot/cold water under pressure
- 1 Gas cooker 2 burners - Stainless steel oven on gimbal - Stainless steel protection handrail
- 1 Cool box 75 L / 20 US Gal/top opening (refrigeration unit included in trim level)
- Cupboard - Storage and lockers
- 1 Double dustbin: 2 x 15L / 4 US Gal
- 2 LED ceiling lights
- 1 Opening portlight with curtains in the coachroof side window

**CHART TABLE - STARBOARD (OPTIONAL EXTRA)**

- Chart table with folding tray against the starboard bulkhead with shelves fitted with fiddles in the upper part
- Electrical panel nearby
- 1 Swivelling LED reading light

**FORWARD CABIN**

Headroom: 1,85m / 6'1"

- Double access door
- Double bed (2,00m x 1,90 - 0,50m / 6'7" x 6'3" - 1'8")
- Mattress in 2 parts (thickness: 10 cm)
- 2 Cupboards: 1 Port hanging locker - Starboard shelves - Open shelves above
- Open top shelves 2 sides of the bed
- 2 LED reading lights
- Indirect LED lighting under shelving along the hull
- 1 Opening hatch with air vent, T44

**AFT CABIN**

Headroom: 1,89m / 6'2"

- Double bed (2,00 - 1,85m x 1,60 - 1,35m / 6'7" - 6'1" x 5'3" - 4'5")
- 1 Cupboard with shelves - Open shelves above
- Open high shelving along the hull
- 2 LED reading lights
- Indirect LED lighting under shelving along the hull
- 2 Opening portholes on the cockpit seat back and on the coachroof

**AFT HEAD - STARBOARD**

Headroom: 1,88m / 6'2"

- Access through saloon
- Work top with built-in basin
- 1 Mixing tap hot/cold water
- 1 Hot and cold cockpit shower
- 1 Manual marine toilet with 80 L / 21 US Gal rigid reserve
- 1 Mirror
- Toilet accessories
- Cupboard, storage, shelving
- 1 LED ceiling light
- Indirect LED lighting under shelving along the hull
- 1 Opening portlight with curtains in the coachroof side window
- 1 Shower curtain

## ENGINE

---

- Engine Yanmar Diesel (Propeller shaft):
  - 14 HP/14 HP (standard)
  - 21 HP/21 HP (Option)

**Boat approved only for inland waterways navigation with the 14 HP engine.**

**The use of the boat is strictly limited to sailing in inland waters only (inland waters applies to rivers, canals, lakes and ponds situated inland of the low water line). In general, all calm waters, without current or chop, where the low power of the engine is sufficient to manoeuvre the boat.**

- Engine control - Control panel in cockpit, starboard
- Engine compartment: Soundproofing foam - Ventilation: 2 air intakes and 1 forced air outlets
- 1 Alternator (12V / 125 Ah)
- 1 Rotomoulded diesel tank 130 L / 34 US Gal (under the sail locker) - Gauge on electrical panel - 1 Deck filler
- Filters: Seawater - Diesel - Water separator
- Stainless steel shaft line
- Fixed two-blade propeller
- 1 Engine access through companionway (opening with 2 gas struts)
- 2 Access to side engine: Head & Aft cabin

## ELECTRICITY

---

- 12V circuit
- 1 Service battery (80 Amps) - 1 Engine battery (50 Amps)
- 1 Power distributor
- 12 V Electrical panel (Fuses - Voltmeter - 1 Fuel gauge)
- 1 USB port dual port, in the saloon
- LED lighting: Overhead lights & Indirect lighting - Cabin and chart table reading lights
- LED navigation lights: 1 Masthead light - 1 Engine navigation light - 1 Anchor light on masthead

## PLUMBING

---

- 1 Rotomoulded freshwater tank 160 L / 42 US Gal, under berth in forward cabin
- Manual gauge on the tank
- Deck filler, stainless steel
- Pressurised electric water pump - Expansion tank - Inline filter
- 1 25 L / 7 US Gal Electric water heater (engine use)
- 1 80 L / 21 US Gal rigid holding tank
- Electric shower drain pump
- 1 Electric bilge pump - 1 Manual bilge pump

## GAS

---

- 1 Gas cylinder locker - starboard aft cockpit (25 cm x 27 cm x 40 cm / 10" x 11" x 15")
- Regulator and safety tap
- Gas leak detector

## TRIM LEVEL & PACKS

### TRIM LEVEL

#### CONFORT TRIM LEVEL

- Natural solid wood decked aft platform with manual opening, 1 Retractable stainless steel swimming ladder
- Polyester drop-leaf cockpit table
- 2 halyard bags
- Blinds / mosquito nets on 2 deck panels, blackout curtains on hull portholes, curtains on coaming windows, curtains and mosquito nets on opening portholes of the aft cabin
- Galley: 12 V refrigeration unit in icebox
- HiFi: Player Fusion + Interior loudspeakers & Waterproof exterior speakers
- Full 12/230 V system (1 Internal socket on the electrical panel, 1 USB socket in the cabins, 25 Amperes battery charger, 1 80 Amp extra battery, Shore power socket)

### ELECTRONICS PACKS: B&G

#### PACK COASTAL

- 1 Triton 2 Graphic display, to starboard from the companionway
- Sensor (Log, Speedometer, Temperature)
- Wind Sensor (Windvane, Anemometer)
- Windex Windvane

#### PACK OFFSHORE

- Chart table: B&G V60 VHF, AIS receiver function
- Multifunction touchscreen Zeus<sup>3</sup> 7" wide wireless (GPS, Chart plotter, Card reader - Navionics Silver cartography included) to starboard from the companionway

### RIGGING PACKS

	PACK DOWNWIND	PACK UPWIND	PACK DOWNWIND + UPWIND
• 2 Genoa winches (H35.2 STA)	■	■	■
• 1 Self tailing manoeuvring winch (H20.1 STA) on the roof (starboard) + blockers	■		■
• Symmetrical spinnaker rigging / Code 0	■		■
• Polyester bowsprit with integrated anchoring gear and bobstay (for Code 0 and asymmetric spinnaker use)	■		■
• Genoa sheet tracks on side decks		■	■
• Furling Dacron genoa (to replace the standard self-tacking jib)		■	■

## OPTIONS

### NAVIGATION ELECTRONICS: B&G

---

- B&G NAC3 autopilot + WR10 Smart Wifi Control

### RIGGING - SAILS

---

- Anodized mast furling system with Dacron mainsail
- Code 0 with Mylar Taffetas furler

### INTERIOR EQUIPMENT

---

- Interior upholstery: Marlin Weiss PVC
- Chart table furniture in the starboard saloon
- Wooden companionway steps
- Foot pump fresh / sea water
- Yacht Case - Tableware
- Forced air heating fuel
- 12V / 230V inverter (700 VA)

### HULL - DECK - COCKPIT

---

- Ballasted boat version
- Fixed keel shallow draught version
- Grey "Perle" hull
- Double steering wheel version
- Cockpit table cover
- Solid wood decking on cockpit sole
- Steering wheels covers (White PVC)
- Silver Coachroof sprayhood
- Silver Cockpit Bimini
- Dolce 51 Cockpit cushions
- 3 folding blades propeller (with 21 CV engine only)
- Rope cutter
- 700 W Electric windlass - Remote control
- Shore fresh water supply
- Cockpit shower (hot/cold water)
- Outboard engine bracket (Pushpit)
- Complete mooring kit
- Aft transom protection